

Regular Reverse Diamond Expanded Metal

CARBON STEEL - ASTM A 1011

Style	Weight in lbs. per C.S.F.		Standard Sizes in Feet		Size of Openings in inches		Center to Center of Bond in inches		Size of Strands in inches		Percent Open Area	No. of Diamonds per ft.		Overall Height in inches
	Plain		SWD	LWD	SWO	LWO	SWD	LWD	Width	Thickness		SWD	LWD	
3/32 - 24L	47		8	4	0.070	0.156	0.128	0.250	0.030	0.024	53	94	48	0.046
3/32 - 24H	71		8	4	0.050	0.156	0.128	0.250	0.045	0.024	30	94	48	0.051
3/16 - 22	56		8	4	0.110	0.313	0.206	0.500	0.047	0.030	55	58	24	0.070
3/16 - 20	90		8	4	0.080	0.313	0.206	0.500	0.063	0.036	40	58	24	0.080
1/4 - 20	86		8	4	0.125	0.618	0.250	1.000	0.072	0.036	42	48	12	0.135
1/4 - 18	114		8	4	0.110	0.618	0.250	1.000	0.072	0.048	42	48	12	0.147
5/16 - 20	52		8	4	0.235	0.730	0.333	1.000	0.063	0.036	62	36	16	0.125
5/16 - 18	113		8	4	0.180	0.670	0.333	1.000	0.094	0.048	44	36	16	0.170

Please contact 9a^VW EFSW9dSf[Yl; Ufor custom sizes

Flattened Reverse Diamond Expanded Metal

CARBON STEEL - ASTM A 1011

Style	Weight in lbs. per C.S.F.		Standard Sizes in Feet		Size of Openings in inches		Center to Center of Bond in inches		Size of Strands in inches		Percent Open Area	No. of Diamonds per ft.		Overall Height in inches
	Plain	Galv.	SWD	LWD	SWO	LWO	SWD	LWD	Width	Thickness		SWD	LWD	
3/16 - 22F	64	-	8	4	0.115	0.343	0.226	0.500	0.058	0.027	49	53	24	0.027
3/16 - 20F	83	-	8	4	0.107	0.343	0.226	0.500	0.063	0.032	44	53	24	0.032
1/4 - 20F	85	-	8	4	0.125	0.625	0.280	1.000	0.079	0.035	43	43	12	0.137
1/4 - 18F	115	-	8	4	0.125	0.625	0.280	1.000	0.080	0.045	43	43	12	0.045
5/16 - 20F	58	-	8	4	0.220	0.720	0.387	1.000	0.075	0.035	61	31	12	0.035
5/16 - 18F	102	-	8	4	0.200	0.720	0.387	1.000	0.099	0.045	49	31	12	0.045
1/2 - 20F	40	51	8	4	0.425	0.925	0.600	1.200	0.079	0.030	73	20	10	0.030
1/2 - 18F	64	83	8	4	0.400	0.925	0.600	1.200	0.097	0.045	68	20	10	0.045
1/2 - 16F	80	98	8	4	0.400	0.925	0.600	1.200	0.096	0.055	68	20	10	0.055
1/2 - 13F	111	130	8	4	0.365	0.825	0.600	1.200	0.107	0.070	64	20	10	0.070
1/2 - 13(.188)F	215	234	8	4	0.185	0.750	0.550	1.200	0.188	0.070	31	22	10	0.070
3/4 - 16F	51	57	8	4	0.860	1.625	1.100	2.000	0.111	0.050	79	11	6	0.050
3/4 - 13F	62	76	8	4	0.850	1.625	1.090	2.000	0.106	0.070	80	11	6	0.070
3/4 - 10(13)F	92	128	8	4	0.780	1.610	1.100	2.000	0.160	0.070	70	11	6	0.070
3/4 - 9(11)F	147	175	8	4	0.730	1.550	1.060	2.000	0.160	0.115	70	11	6	0.115
3/4 - 11HF	258	279	8	4	0.420	1.310	0.875	2.000	0.221	0.115	48	14	6	0.115
1 - 16F	41	47	8	4	0.980	1.925	1.175	2.375	0.098	0.050	84	10	5	0.050
1 - 14F	65	72	8	4	0.960	1.900	1.225	2.375	0.125	0.070	80	10	5	0.070
1 - 12F	98	113	8	4	0.900	1.850	1.200	2.375	0.156	0.085	74	10	5	0.085
1 - 10F	133	144	8	4	0.830	1.820	1.190	2.375	0.160	0.115	73	10	5	0.115
1 1/2 - 16F	40	44	8	4	1.280	2.530	1.510	3.000	0.119	0.055	84	8	4	0.055
1 1/2 - 13F	48	66	8	4	1.300	2.570	1.550	3.000	0.116	0.070	85	8	4	0.070
1 1/2 - 12F	58	76	8	4	1.270	2.520	1.510	3.000	0.116	0.085	85	8	4	0.085
1 1/2 - 9(10)F	105	125	8	4	1.750	2.430	1.500	3.000	0.158	0.115	79	8	4	0.115
1 1/2 - 10F	125	136	8	4	1.150	2.390	1.500	3.000	0.188	0.115	75	8	4	0.115

Please contact 9a^VW EFSW9dSf[Yl; Ufor custom sizes

Reverse Diamond manufactured in Canada ONLY