

Flattened Reverse Diamond Expanded Metal

STAINLESS STEEL FLATTENED - TYPE 304 (Available in T-304L, T-316, T-316L)

Style	Weight in lbs. per C.S.F Plain	Standard Sizes in Feet		Size of Openings in inches		Center to Center of Bond in inches		Size of Strands in inches		Percent Open Area	No. of Diamonds per ft.		Overall Height in inches
		SWD	LWD	SWO	LWO	SWD	LWD	Width	Thickness		SWD	LWD	
3/16 - 22F	40	8	4	0.185	0.375	0.293	0.500	0.047	0.029	68	41	24	0.029
3/16 - 20F	47	8	4	0.185	0.375	0.293	0.500	0.047	0.035	68	41	24	0.035
1/2 - 18F	64	8	4	0.380	0.870	0.570	1.200	0.091	0.040	68	21	10	0.040
1/2 - 16F	80	8	4	0.380	0.870	0.570	1.200	0.091	0.050	68	21	10	0.050
1/2 - 13F	143	8	4	0.305	0.865	0.570	1.200	0.130	0.070	55	21	10	0.070
3/4 - 16F	57	8	4	0.795	1.650	1.040	2.000	0.118	0.050	77	11.5	6	0.050
3/4 - 13F	72	8	4	0.793	1.650	1.040	2.000	0.120	0.070	77	11.5	6	0.070
3/4 - 9(10)F	143	8	4	0.775	1.600	1.091	2.000	0.155	0.115	71	11	6	0.115
1 1/2 - 16F	40	8	4	1.265	2.580	1.500	3.000	0.119	0.050	84	8	4	0.050
1 1/2 - 13F	51	8	4	1.220	2.585	1.500	3.000	0.121	0.070	84	8	4	0.070
1 1/2 - 9(10)F	111	8	4	1.150	2.410	1.500	3.000	0.165	0.115	78	8	4	0.115

ALUMINUM FLATTENED - ALLOY 3003 H14 (Available in 5005 H34)

Style	Weight in lbs. per C.S.F Plain	Standard Sizes in Feet		Size of Openings in inches		Center to Center of Bond in inches		Size of Strands in inches		Percent Open Area	No. of Diamonds per ft.		Overall Height in inches
		SWD	LWD	SWO	LWO	SWD	LWD	Width	Thickness		SWD	LWD	
3/16 - .032F	24	8	4	0.110	0.325	0.226	0.500	0.060	0.032	47	53	24	0.032
5/16 - .032F	20	8	4	0.205	0.725	0.375	1.000	0.082	0.032	56	32	12	0.032
1/2 - .051F	23	8	4	0.390	0.900	0.570	1.200	0.091	0.051	68	21	10	0.051
1/2 - .081F	37	8	4	0.390	0.900	0.570	1.200	0.091	0.081	68	21	10	0.081
3/4 - .051F	16	8	4	0.815	1.685	1.090	2.000	0.122	0.051	78	11	6	0.051
3/4 - .081-LF	28	8	4	0.795	1.600	1.090	2.000	0.134	0.081	76	11	6	0.081
3/4 - .081-HF	38	8	4	0.730	1.560	1.090	2.000	0.181	0.081	67	11	6	0.081
3/4 - .125F	62	8	4	0.720	1.500	1.090	2.000	0.187	0.120	66	11	6	0.120
3/4 - .188F	105	8	4	0.705	1.465	1.150	2.000	0.221	0.180	61	10.5	6	0.180
1 1/2 - .081F	22	8	4	1.250	2.560	1.525	3.000	0.143	0.081	81	8	4	0.081
1 1/2 - .125F	43	8	4	1.145	2.460	1.500	3.000	0.181	0.120	76	8	4	0.120

Please contact Golden State Grating, Inc for custom sizes

Reverse Diamond manufactured in Canada ONLY